



FAMED LODZ S.A

Excellence through experience,
for over 75 years.

SOLIS 160F

practical, modern, reliable

SOLIS 160 is the perfect compromise between quality and price of the operating lamps, which will satisfy even the most demanding user. The round shape of the dome allows accurate surface disinfection.

The system of three independent domes provides excellent illumination of the treatment and its shadowlessness. Handy sterile handle allows accurate positioning of the device and adjusting the size of the light field of the operating field.

Ergonomic design and reduced weight of the operating lamp **SOLIS 160** ensures comfortable handling while enabling any application both in emergency departments as well as specialized operating rooms.

Lighting modules with LEDs are covered by extremely robust plate of polycarbonate, to protect against accidental damage, and its flat shape facilitates the work of the operator. Lamps **SOLIS 160** have a wide range of adjustment due to the possibility of rotation relative to the four axes.

Illuminance of 160,000 lux at a distance of 1 meter. In a series of lamps **SOLIS 160** was used innovative system of LEDs which form a light module, in three independently powered sections.

In case of failure of one of the sections, the other two provide a very good level of lighting.

The dome does not contain any external screws or other fasteners.




Control Panel - easy to use, with a push button on / off and adjust the light intensity.

The sterile handle for focusing light field in the operating field, having ergonomic design, placed in the center provides easy access and positioning the dome.



Technical data:



Distributor :

PT. CIPTA VARIA KHARISMA UTAMA

Jl. Utan Kayu no. 105A, Jakarta

Telp. : +62 21 8511 303

Fax. : +62 21 8507 633

E-mail : kharisma-utama@kharisma-utama.com

Lighthead	SOLIS 160
Supply voltage of the lighthead	24V DC
Supply voltage of the lamp [AC]	100-240V 50-60Hz
Light intensity at a distance of 1 m (Ec)	160 000 lx
Adjustable light intensity	25 ÷ 100%
Colour rendering index CRI	96
Colour temperature	4000 K ± 8%
Operating field diameter d10	220 mm
Light spot diameter d50	110 mm
Adjustable diameter of the operating field	yes
Temperature increase near surgeon's head	< 1°C
Depth of illumination L1+L2	70 cm
Power consumption	70 VA
Life time of the light source	up to 40.000 h
Built in, battery with charger	No
protection degree provided by lighthead enclosure and power supply	IP 43 / 20
Automatic change over to battery in case mains supply failure and back again	No

The product complies with the European Directive **MDD 93/42/EEC**

and standards: **IEC 60601-1:2011**
IEC 60601-1-2:2007



FABRYKA APARATURY ELEKTROMEDYCZNEJ

FAMED Łódź S.A.

ul. Szparagowa 2, 91-211 Łódź

Address for correspondence:

ul. Ciasna 21 a

93-531 Łódź, POLAND



www.famed.pl



info@famed.pl



Jarosław **Majchrzak**
+48 784 012 501

j.majchrzak@famed.pl

Filip **Kozłowski**
+48 601 276 583

f.kozlowski@famed.pl

Leszek **Kaniewski**
+48 662 066 064

l.kaniewski@famed.pl